IN THE CLAIMS:

Please amend claims 2 to 12 and 14 to 21 as follows.

- 1. A system for determining and/or positioning a digital sensor of dental X-ray apparatus, comprising
 - an input and output device for interactive control of the system,
 - a first storage area, in which the digital image of the area to be examined, is saved,
 - a second storage area, in which at least one template image of the sensor is stored,
 - a processing unit, which places the template image of at least one sensor simulatively on the area to be examined of the digital image such that when a real X-ray image is created the area to be examined is depicted completely,
 - wherein the processing unit has means for indicating the sensor and the position of the sensor in the digital image.
- 2. (Currently Amended) A system as defined in claim 1, <u>further comprising</u> [characterized by] a user interface enabling interactive selection of the template image and/or the area to be examined.
- 3. (Currently Amended) A system as defined in [any one of claims 1 to 2, characterized] <u>claim 1, comprising</u> in that [the] <u>a</u> user preferably interactively specifies the area to be examined in the digital image, and the processing unit [specifies] <u>is capable of specifying</u>, preferably by iterative simulation, that template image which covers the area to be examined as completely as possible.

- 4. (Currently Amended) A system as defined in [any one or more of the previous claims, characterized in that the position] <u>claim 1</u>, <u>wherein the processing unit is capable of determining the position</u> of the template image [is determined] in one or more dimensions.
- 5. (Currently Amended) A system as defined in [any one or more of the previous claims, characterized by] <u>claim 1, further comprising</u> a computer interface to the X-ray apparatus, via which [the] presettings determined by simulation are transferred, [whilst] <u>while</u> the X-ray apparatus permits the creation of a digital image only when [these] <u>said</u> presettings apply.
- 6. (Currently Amended) A system as defined in [any one or more of the previous claims, characterized by] <u>claim 1</u>, <u>further comprising</u> a computer interface, via which an existing digital image of the patient to be X-rayed is transferred to the first storage area.
- 7. (Currently Amended) A system as defined in [any one or more of the previous claims, characterized in that] <u>claim 1, wherein the apparatus</u> comprises a dental X-ray-unit [is controlled].
- 8. (Currently Amended) A system as defined in [any one or more of the previous claims, characterized in that] <u>claim 1, wherein</u> the system [is in the form of] <u>comprises</u> a PC controlled by software.
- 9. (Currently Amended) A template for specifying a digital X-ray sensor, [characterized by the] wherein a shape and size of an X-ray image is created using [the] an assigned digital X-ray sensor.
- 10. (Currently Amended) A template as defined in claim 9, [characterized by] comprising a property making it possible to pass the template over an X-ray image.

- 11. (Currently Amended) A template as defined in claim 10, [characterized by] comprising a digitally stored size and orientation which is adapted, when called on, in accordance with [the] actual dimensions of a digital X-ray image.
- 12. (Currently Amended) A template as defined in claim 10, [characterized by] comprising a frame [and/or by a] of transparent material.
- 13. A method of specifying and/or positioning a digital sensor of dental X-ray apparatus using templates corresponding in size and shape to the sensor image, comprising
 - a first step, in which the X-ray image is selected, this preferably being an X-ray image of the patient to be examined,
 - a second step, during which the area to be imaged is specified,
 - a third step, during which there is selected, from a plurality of templates each of which is assigned to sensors of the digital X-ray apparatus, that template which covers the area specified in the second step most precisely.
- 14. (Currently Amended) A method as defined in claim 13, [characterized in that] wherein the third step is carried out automatically or interactively.
- 15. (Currently Amended) A method for specifying and/or positioning a digital sensor of dental X-ray apparatus, using templates corresponding in size and shape to [the sensor] an image of the sensor, comprising
 - a first step, in which the X-ray image is selected, this preferably being

an X-ray image of the patient to be examined,

- a second step, during which there is selected, from a plurality of templates each assigned to a sensor of the digital X-ray apparatus, that template which should be used to cover the area to be X-rayed,
- and a third step, during which the template is moved across the X-ray image for purposes of control and the imaging area appertaining to the template is thus revealed, the second and third steps being iteratively continued until a suitable combination of sensor and imaging area is displayed.
- 16. (Currently Amended) A method as defined in [any one of claims 13 to 15, characterized in that] <u>claim 13, wherein</u> the X-ray [images] <u>image</u> and the templates are managed in digital form.
- 17. (New) A method as defined in claim 15, wherein the X-ray image and the templates are managed in digital form.
- 18. (Currently Amended) A method for creating a number of partial images using at least one sensor, comprising, a first step in which several areas to be X-rayed are selected from an image, and a second step in which there is effected automatic selection and display of the sensor suitable for creating the respective image.
- 19. (Currently Amended) A method as defined in claim 17, wherein that the image is a digital panoramic radiogram, which is displayed on a digital display unit and refers individually to the patient.
- 20. (Currently Amended) A method as defined in claim 17, wherein a suitable sequence for making the images is automatically proposed, account being taken of particular conditions of the respective X-raying situation,

namely the order of the images to be created, the operation of positioning the X-ray unit and/or the selection of a sensor type.

- 21. (Currently Amended) A data medium, containing a data structure that is capable of running on a computer to carry a method as defined claim 13.
- 22. (New) A data medium, containing a data structure that is capable of running on a computer to carry a method as defined claim 15.
- 23. (New) A data medium, containing a data structure that is capable of running on a computer to carry a method as defined claim 18.